

FIELD

Environmental Instruments

Equipment Rental and Field Supplies

Proactive

Hurricane Five-Stage Sampling Pump

"Your Needs Are Our Business"

Toll-Free
800-393-4009



For even deeper wells, ProActive introduces the Hurricane. The Hurricane is capable of pumping up to 150 feet from ground level by simply connecting the pump to our revolutionary Low Flow With Power Booster II Controller, or Power Booster II Controller (controller rented or sold separately).

The Hurricane will make your next groundwater sampling event go much quicker when it comes to purging a well. And with the Low Flow With Power Booster II Controller, the field technician now has the ability to control the flow of water being discharged from the Hurricane thus, keeping up with EPA groundwater standards for Low Flow Sampling.

The Hurricane's reliable design is suitable for continuous sampling or purging of groundwater wells.

Features

- Passes sand, small rocks and debris without clogging or damaging the pump motors!
- Runs continuously without the need for a cool down! Unlike, the competition.
- Runs dry for up to two hours without motor damage!
- Contains a 400 hour motor life.
- Uses a sleek outside shell that minimizes well hang-ups.
- Comes ready for field use - with 150' of heavy-duty wire and alligator battery connectors.

SPECIFICATIONS

Hurricane Pump Chart

<i>PUMPING DEPTH</i>	<i>GPM</i>
10	4.50
20	4.00
40	3.00
50	2.75
70	2.25
80	2.00
100	1.35
110	1.25
120	1.15
140	.50
150	.25
160	N/A

POWER CONSUMPTION:	510 WATTS (MAX)
VOLTAGE RECOMMENDATION:	12 - 15 At Source
MAXIMUM AMP OUTPUT:	34 AMPS
MEASUREMENTS:	LENGTH 26" DIAMETER: 1.82"
CONSTRUCTED:	ABS PLASTIC & STAINLESS STEEL
DISCHARGE OUTLET:	3/8" ID x 1/2" OD
SUPPLIED WITH:	160' HEAVY DUTY 10 GAUGE WIRE, GREEN CONNECTOR

301 Brushton Avenue
Suite A
Pittsburgh, PA 15221

800-393-4009

Fax 412-436-2616

info@
fieldenvironmental.com

fieldenvironmental.com

Inquiries and
orders

800-393-4009