



FIELD ENVIRONMENTAL INSTRUMENTS, INC.

www.fieldenvironmental.com

301 Brushton Avenue
Suite A
Pittsburgh PA 15221
800-393-4009 Toll Free
(412) 436-2600 Local
(412) 436-2616 Fax

ProActive Environmental Products new 12 Volt SS-HURRICANE pump is now available for re-sale! Pumps 150 feet!

ProActive Environmental Products continues to pursue its MISSION of designing safe and reliable low voltage groundwater submersible pumps. ProActive is proud to engineer the SS-Hurricane 12-volt stainless steel pump for low flow sampling or ground water purging of monitoring wells. Its sleek design eliminates well hang ups and fits easily into a 2" monitoring well or larger.

SIMPLE TO USE AND EXTREMELY POWERFUL

The SS-HURRICANE is capable of pumping up to 150 feet from ground level to water level. Simply, connect the pump connector to the Low Flow with Power Booster 2.5 "LCD" Controller, then to a 12 volt battery, energizing the pump. Sound Simple? We think so.

For the Harsh Environments

Designed for the Field Technician in mind, the SS-HURRICANE can handle the daily field riggers that are associated with ground water or remote water sampling. With its complete high polished stainless steel body and components, you can rest assure that the SS-HURRICANE will not rust or corrode under normal working conditions. Low cost, low maintenance and ease of use make the SS-HURRICANE the preferred choice for groundwater purging or low flow sampling.

Why Choose the SS-HURRICANE?

Simple to use! Runs off a 12 volt DC car battery.

Lifts up to 150 feet deep from ground level to water level!

Reliable design is suitable for continuous sampling or purging of groundwater wells.

Low Flow Sample as low as 10 ML per minute, from any depth, when using the Low Flow with Power Booster 2.5 "LCD" Controller.

Easy to read, LCD display conveniently placed on top of the Low Flow with Power Booster 2.5 "LCD" Controller makes adjusting and reading the discharge rate a breeze!

Computer engineered bottom debris filter screen minimizes passing sand, small rocks and debris, reducing clogging or damaging the pump motor!

Long lasting, high performance pump motor lasts over 400 hours under normal working conditions.

Simple to clean and decontaminate!

The SS-HURRICANE is only 1.82" OD and constructed of three high polished stainless steel parts:

1. The replaceable motor module
2. The motor housing top connector
3. The outside pump housing

Pumping Depth and Volume Chart

Feet	g.p.m.
3	3.75
10	3.25
20	3.0
30	3.0
40	3.0
60	2.5
70	2.0
80	1.5
100	1.25
110	1.25
120	1.0
130	.85
150	.50
160	N/A

