Environmental **Instruments**

Equipment Rental and Field Supplies

"Your Needs Are Our Business"

FIELD

Toll-Free 800-393-4009

The Monsoon pump is capable of pumping up to 120 feet from ground level by connecting the pump to the Power Booster II Controller or The Low Flow With Power Booster II Contoller.

This will make your next groundwater sampling event go much quicker when it comes to purging a well. With the Low Flow Power Booster II Controller, the field technician now has the ability to controll the flow of water being discharged from the Monsoon thus, keeping up with EPA groundwater standards for low flow sampling.

Features

- □ Passes sand, small rocks and debris without clogging or damaging the pump motors!
- \Box Runs continously without the need for a cool down! Unlike, the competition.
- $\hfill\square$ Runs dry for up to two hours without motor damage!
- Contains a 500 hour motor life.
- $\hfill\square$ Uses a sleek outside shell that minimizes well hang-ups.
- Comes ready for field use with 130' of heavy-duty wire and alligator battery connectors.

Monsoon Pump Chart PUMPING DEPTH IN FEET GALLONS PER MINUTE		301 Brushton Avenue Suite A Pittsburgh, PA 15221
$egin{array}{ccc} & 10 \ & 20 \end{array}$	4.4 4.2	800-393-4009 Fax 412-436-2616
$\begin{array}{ccc} \square & 40 \\ \square & 50 \end{array}$	3.5 2.8	info@
$ \begin{array}{ccc} & 70 \\ & 80 \\ & 85 \end{array} $	2.1 1.9	fieldenvironmental.com
$\begin{array}{ccc} & 33 \\ \Box & 100 \\ \Box & 110 \end{array}$	1.6 1.5 1.25	Visit us on the web www.
	1.0 N/A	fieldenvironmental.com Inquiries and
POWER CONSUMPTION:	450 WATTS (MAX)	orders
VOLTAGE RECOMMENDATION: MAXIMUM AMP OUTPUT:	12 – 15 At Source 30 AMPS	800-393-4009
MEASUREMENTS: CONSTRUCTED:	LENGTH 20" DIAMETER: 1.82" ABS PLASTIC & STAINLESS STEEL	
DISCHARGE OUTLET: SUPPLIED WITH:	3/8" ID x 1/2" OD 130' OF HEAVY DUTY 12 GAUGE WIRE & BATTERY CLAMI	



SPECIFICATIONS

Proactive

Four-Stage Sampling Pump

Monsoon