

# FIELD

## Environmental Instruments

### Proactive

Equipment Rental and Field Supplies

Stainless Steel  
Mega-Monsoon Sampling Pump

*"Your Needs Are Our Business"*

Toll-Free  
**800-393-4009**



ProActive is proud to engineer the SS-Mega-Monsoon 12-volt stainless steel pump for low flow sampling or ground water purging of monitoring wells. Its sleek design eliminates well hang ups and fits easily into a 2" monitoring well or larger.

The SS-Mega-Monsoon is capable of pumping up to 200 feet from ground level. Simply, connect the pump connector to the Low Flow with Power Booster III "LCD" Controller, then to a 12 volt battery, energizing the pump.

Designed for the Field Technician in mind, the SS-Mega-Monsoon can handle the daily field riggers that are associated with ground water or remote water sampling. With its complete high polished stainless steel body and components, you can rest assure that the SS-Mega-Monsoon will not rust or corrode under normal working conditions. Low cost, low maintenance and ease of use make the SS-Mega-Monsoon the preferred choice for groundwater purging or low flow sampling.

## SPECIFICATIONS

The SS-Mega-Monsoon is only 1.82" OD and constructed of three high-polished stainless steel parts

1. The replaceable motor module
2. The motor housing top connector
3. The outside pump housing



Ready for field use: Supplied with 190 feet of heavy duty wire neatly rolled up on a sturdy high impact metal reel, pump holster and Low Flow with Power Booster III adapter.

Low cost, Low maintenance, and ease of use make the SS-Mega-Monsoon the preferred choice for groundwater purging or low flow sampling.

Should the motor fail, the field technician can change out the SS-Mega-Monsoon motor in less than 60 seconds! And to start you off with; the SS-Mega-Monsoon comes complete with one additional motor module. In essence, you will be receiving two pumps for the price of one! The main wear out parts consisting of the motor and seal all have been incorporated in a single replaceable motor module. Should the existing replaceable motor module fail in the field, a new replaceable motor module can quickly be installed within 60 seconds by a simple quarter turn twist! Once installed, your pump is essentially new and will have a life span identical to a new pump.

<b>POWER CONSUMPTION:</b>	480 WATTS (MAX)
<b>VOLTAGE RECOMMENDATION:</b>	12 – 15 At Source
<b>MAXIMUM AMP OUTPUT:</b>	20 AMPS
<b>MEASUREMENTS:</b>	LENGTH 6.5" ..... DIAMETER: 1.82"
<b>CONSTRUCTED:</b>	High Polish Stainless Steel
<b>DISCHARGE OUTLET:</b>	3/8" ID x 1/2" OD
<b>SUPPLIED WITH:</b>	210' OF HEAVY DUTY PVC wire neatly rolled up on a sturdy high impact metal reel, pump holster and Low Flow with Power Booster III adapter

301 Brushton Avenue  
Suite A  
Pittsburgh, PA 15221

800-393-4009

Fax 412-436-2616

info@  
fieldenvironmental.com

Visit us the web  
www.  
fieldenvironmental.com

Inquiries and  
orders  
**800-393-4009**